

APC Products Limited

www.pailclosures.com

Tel: 905-457-0887

Fax:905-459-3983

APC-2-AG PRODUCT SPECIFICATION 9-2-AG

DESCRIPTION	APC-2-AG ANTI-GLUG PLASTIC PAIL CLOSURE
PART NUMBERS	APC-25-AG fits 6 mm minimum cover bead height (standard part) APC-25-AG-NP fits 5 mm minimum cover bead height (NP cap option)
PART DRAWINGS	AD9-2-AG Rev 7 APC-2-AG Anti Glug Closure
CLOSURE SIZE	38 mm (1.5 inch) neck thread diameter 44 mm (1.8 inch) body height extended
COVER OPENING	65 mm (2.56 inch) cover beaded rim outside diameter AD9-2.4 Rev 3 APC-1, APC-2 & APC-4 Cover Opening
CLOSURE WEIGHT	28 Grams +/- 1
MATERIAL & COLOR	FDA approved virgin resins CAP – high density polyethylene, white BODY – EVA co-polymer low density polyethylene, natural
TAMPER EVIDENCE	CAP – 4 tabs must be broken to lift 2 bails BODY – internal diaphragm with pull ring molded into spout
INSTALLATION	Same as APC-2 installation
PERFORMANCE *	Hydrostatic leak test target: 30 kPa (4.5 psi) water for 30 minutes Eight tabs fold inward as closure is opened. Flow control reduces glugging, splashing and clean-up.
APPLICATION *	The closure is designed for UN Packing Group II and III applications up to 30 kPa subject to performance and product compatibility testing. Do not use for hot fill applications or UN Packing Group I applications.
CONTROL OF CHANGE	Specifications are subject to change. APC-2-AG buyers on record will be notified.

* These product specifications are intended as a guide only. Closures are manufactured under a TS16949 quality program. Sample closures are available for product testing. It is the responsibility of the buyer and filler to ensure the closure meets the product compatibility and performance requirements for both regulated and non-regulated packaging applications.