APC Products Limited

www.pailclosures.com Tel: 905-457-0887

APC-4L PRODUCT SPECIFICATION

| DESCRIPTION | APC-4L PAINT CAP CLOSURE |
|----------------------|--|
| PART NUMBERS | APC- 4L |
| PART DRAWINGS | AD9-4.1 Rev 3 APC-4L Plastic Paint Cap |
| CLOSURE SIZE | 69 mm (2.72 inch) outside diameter 34 mm (1.38 inch) long handle 11.3 mm (0.47 inch) thick |
| COVER OPENING | 2.56 inch cover beaded rim outside diameter 0.24 to 0.28 inch cover bead height See AD9-2.4 Rev 5 APC-25 & APC-4L Cover Opening drawing |
| CLOSURE WEIGHT | 9 Grams +/- 1 |
| MATERIAL & COLOR | FDA approved virgin resins 50% LLDPE, 47% LDPE, 3% EVA Natural color |
| INSTALLATION | Closures are supplied by APC with the handle in the "unlatched" position See APC web site <u>www.pailclosures.com</u> / installation Fold and latch handle Use installation press to fit onto warm or cold molded plastic covers. |
| PERFORMANCE * | Hydrostatic leak test target: 20 kPa (3 psi) water for 5 minutes |
| APPLICATION * | The closure is designed latex paint and similar non-hazardous products in plastic pails. Do not use for hot fills or UN Packing Group applications. |
| CONTROL OF CHANGE | Specifications are subject to change. APC-4L buyers on record will be notified. |

* These product specifications are intended as a guide only. Closures are manufactured under an ISO 9001:2015 management program. Sample closures are available for product testing. It is the responsibility of the buyer and filler to ensure the closure meets the product compatibility and performance requirements for both regulated and non-regulated packaging applications.

Exhibit 9-4.1

Rev 7 12-2022