

APC Products Limited

www.pailclosures.com

Tel: 905-457-0887

APC-7-AG PRODUCT SPECIFICATION

DESCRIPTION	APC-7-AG ANTI-GLUG INSERT MOLDED PAIL CLOSURE
PART NUMBERS	APC-7-AG
PART DRAWINGS	AD9-7-AG Rev 0 APC-7-AG Anti Glug Insert Molded Closure
CLOSURE SIZE	38 mm (1.5 inch) neck thread diameter, 6 threads per inch 44 mm (1.8 inch) body height extended
COVER OPENING	66 mm (2.6 inch) clamp inserts outside diameter. New cover (lid) mold core and cavity inserts required. APC Products Ltd can provide drawings for insert tooling.
CLOSURE WEIGHT	22 Grams +/- 1
MATERIAL & COLOR	FDA approved virgin resins CAP – high density polyethylene, white BODY – EVA co-polymer low density polyethylene, natural
TAMPER EVIDENCE	CAP – 4 tabs must be broken to lift 2 bails BODY – plastic lid molded around body outer skirt - internal diaphragm with pull ring molded into spout neck
INSTALLATION	Same as APC-7 installation See APC web site www.pailclosures.com / installation
PERFORMANCE *	Hydrostatic leak test target: 30 kPa (4.5 psi) water for 30 minutes. Eight tabs fold inward as closure is opened and body is extended. Flow control reduces glugging, splashing and clean-up.
APPLICATION *	The closure is designed for UN Packing Group II and III applications up to 30 kPa subject to performance and product compatibility testing. Do not use for hot fill applications or UN Packing Group I applications.
CONTROL OF CHANGE	Specifications are subject to change. APC-7-AG buyers on record will be notified.
AVAILABILITY	Closures are currently available for customer testing and field trials.

* These product specifications are intended as a guide only. Closures are manufactured under an ISO 9001:2015 management program. Sample closures are available for product testing. It is the responsibility of the buyer and filler to ensure the closure meets the product compatibility and performance requirements for both regulated and non-regulated packaging applications.